## **Product Specifications**

## FlashCheck. Lollipop Auto Cal Min/Max Antimicrobial Thermometer

Measurement Range	e -40°F to 311°F (-40°C to 155°C)	
Operating Range	32°F to 122°F (0°C to 50°C)	
Accuracy	±0.9°F from -40°F to +14°F (±0.5°C from -40°C to -10°C) ±0.5°F from +14°F to +68°F (±0.3°C from -10°C to +20°C) ±0.9°F from +69°F to +239°F (±0.5° from +21°C to +115°C) ±1.8°F from 240°F to +311°F (±1.0°C from 116°C to 155°C)	)°C
Sensor	Thermistor	
Display Resolution	0.1°F /°C	
Display Reading Update	1 second	
Display Window Size	1.3in W x 0.9in H (32.9mm W x 22.9mm H)	
Calibration	Automatic calibration feature	
Battery	Button cell alkaline	
Body Casing	ABS plastic with antimicrobial addit	ive
Probe Length	4.13in (105mm)	
Probe Diameter	0.14in (3.56mm), reduced tip 0.1in (2.5mm)	
Weight	1.3oz (37.6g)	
Waterproof Rating	IP65	
Factory Calibration	NIST traceable calibration certified	
Compliance Certificate	Manufacturers certificate of complia available from DeltaTrak, NIST Traceable, NSF, CE	inc

DeltaTrak manufactures and operates under an ISO 9001:2015 registered quality management system





## Model 11050

Probe protection cap

- Antimicrobial additive inhibits growth of bacteria, mould and fungus
- Min/Max memory stores lowest/highest readings
- Automatic calibration feature
- IP65 Waterproof housing
- Sealed unibody construction
- Small-diameter probe ideal for measuring temperature of "thin mass" food such as meat patties and chicken/fish fillets (FDA Food Code 4-302.12 (B))
- NSF certified
- °F/°C selectable

SS 11050

