

Product Specifications

FlashCheck Waterproof Min/Max Folding Probe Thermometer

| | |
|------------------------|--|
| Measurement Range | -58°F to 572°F (-50°C to 300°C) |
| Operating Range | 32°F to 122°F (0°C to 50°C) |
| Accuracy | ±1.8°F from -58°F to +23°F (±1.0°C from -50°C to -5°C), ±0.5°F from +28°F to +149°F (±0.5°C from -5°C to +65°C), ±1.8°F from 149°F to +572°F (±1.0°C from 65°C to 300°C) |
| Response Time | Under 4 seconds |
| Sensor | Thermistor |
| Display Resolution | 0.2°F / 0.1°C |
| Display Reading Update | Every 0.25 seconds |
| Display Window Size | 1.68 in W x 0.65in H (42.7mm W x 16.6mm H) |
| Calibration | Automatic Calibration button |
| Battery | CR2032 3V Li coin cell battery |
| Auto Shut-Off | 10 minutes |
| Body Casing | ABS Plastic |
| Probe Length | 4.7in (120mm) |
| Probe Diameter | Food grade safety 304 stainless steel probe 0.067in (1.7mm) |
| Waterproof Rating | IP67 |
| Factory Calibration | NIST traceable calibration |



Model 15051

- Instant temperature reading
- Foldable probe for safe handling
- Magnetic back surface
- Hold feature locks temperature reading
- Ideal for thin mass foods such as meat patties, chicken and fish fillets
- Min/Max memory stores lowest/highest readings
- °F/°C selectable
- Measures up to 572°F (300°C)
- Backlit display
- Automatic calibration feature
- Highly visible dual scale jumbo LCD display
- IP67 waterproof, sanitizable, dirt and grease resistant
- Powers on automatically when unfolding probe
- Automatic shut off saves battery life
- Complies with FDA Food Code 4-203.11

DeltaTrak manufactures products under an ISO 9001:2015 registered quality management system

SS 15051

